

MASTER SOLAR


15,25,32 - 8




Max. Flow Rate
3,5 m³/h

Max. Head
8m

Nameplate



Performance Curve




EEI ≤ 0.23

iPWM

ErP
READY

CE RoHS
Compliant

Dimensions



L1 93 mm

L2 126 mm

L3 99 mm

H1 110 mm

H2 130/180 mm

H3 60 mm

Different models

Model	Min/Max Temp (°C)	L (mm) H2	DN G	P1 Max	Voltage (V)	Rated Current (A)	Union
15-8-130	-10 to +110	130	15mm G1	65	1x230	0,65	G1 to G3/4
25-8-130	-10 to +110	130	25mm G1½	65	1x230	0,65	G1½ to G1
25-8-180	-10 to +110	180	25mm G1½	65	1x230	0,65	G1½ to G1
32-8-180	-10 to +110	180	32 mm G2	65	1x230	0,65	G2 to G1¼

TECHNICAL DATA SHEET

MASTER SOLAR

Application

For domestic hot water system such as mix water underfloor heating system, air energy hot water circulation system, solar hot water circulation system and family hot, cold water pressurization circulation, etc.



4-6M EEI ≤ 0.20, 8M EEI ≤ 0.21

iPWM **ErP**
READY

Main features

- 4-6M EEI ≤ 0.20, 8M EEI ≤ 0.21
- Intelligent frequency control
- Compact size, easy for installation
- Proportional pressure mode
- Constant pressure mode
- Constant speed mode
- AUTO adapt mode
- PWM external control optional
- Visualized operation
- Low noise, low temperature

Working condition

- Liquid temperature: 2°C ~ 110°C
- Ambient temperature: 0 ~ +40°C
- Max system pressure: 10bar
- Protection level: IP42
- Rated voltage/frequency: 220V ~ 240V/50Hz
- Insulation class: E
- Pumped liquid characteristics: clean liquid, free from solids and mineral oils, non-toxic, chemically neutral, close to the characteristics of water
- Installation: the motor shaft must be kept in horizontal direction

Functions for different model

Model	Internal control			External control
	PP	CP	CS	PWM
MASTER XX - X - XXX	I	I	I	PWM1
	II	II	II	
	III	III	III	
	AUTO	/	/	
MASTER XX - X - XXX PWM1	/	/	III	PWM1
MASTER XX - X - XXX PWM2	/	/	III	PWM2